

Karakteristika



- Specielt designet applikationer hvor hoveddelen af lufttæppet bliver installeret indeni en kolonne eller skilleplade af arkitektoniske årsager. Det kan blive lodret eller vandret monteret.
- Selvbærende beklædningskonstruktion lavet af galvaniseret stålplader, afsluttet i strukturel hvid epoxy-polyester maling RAL9016 som standard. Andre farver og rustfrit stål er tilgængelige ved anmodning.
- Luftstrømmen fra Invisair følger en lige linje fra luft indtaglamellerne til udledningen. Indtagområdet inde i en skilleplade eller kolonne kan være designet med en passende lamel fremstillet af andre.
- Anodiseret aluminium udtagslameller, airfoil formet, justerbar fra 0 til 15° i vilkårlig retning.
- EC Double-inlet centrifugal fans driven by an external rotor motor and low noise level, with very low consumption efficiency fans.
- "P" type med vandvarmet spole "E" type med elektrisk skjold elementer, tre faser med integreret regulering. "A" type uden varme, kun luft. Mulighed for udvidende DX spole.
- Advanced Plug&Play control. Includes: Advanced PRO control with LCD display and integrated thermostat, door contact, 10m and remote control. With integrated functions: door delay (configurable); interface mode; operation, alarm and maintenance warning signals; and multiple digital inputs that modify the air curtain's operation.
- Includes protective varnish for the electronic board and control.
- Optional:
 - Auxiliary temperature sensors that improve air curtain control and increase energy savings.
 - Clever PRO intelligent control (automatic, programmable, ModBus via PLC, timer, etc.) with an additional temperature sensor.

Specifikationer

50Hz

Uopvarmet		
Model	Nominel luftstrøm (m ³ /h)	Anbefalet installationshøjde (m)
IBB 1000 A	4020	5-7
IBB 1500 A	5360	5-7
IBB 2000 A	8040	5-7
IBB 2500 A	9380	5-7
IBB 3000 A	10720	5-7
ISB 1000 A	3060	3,5-5
ISB 1500 A	4080	3,5-5
ISB 2000 A	6120	3,5-5
ISB 2500 A	7140	3,5-5
ISB 3000 A	8160	3,5-5

Elektrisk varme			
Model	Nominel luftstrøm (m ³ /h)	Elektrisk opvarmingskapacitet 400Vx3 (kW)	Anbefalet installationshøjde (m)
IBB 1000 E	4020	6/15/21	5-7
IBB 1500 E	5360	8/19/27	5-7
IBB 2000 E	8040	12/30/42	5-7
IBB 2500 E	9380	16/30/46	5-7
IBB 3000 E	10720	20/30/50	5-7
ISB 1000 E	3060	5/10/15	3,5-5
ISB 1500 E	4080	7,5/15/22,5	3,5-5
ISB 2000 E	6120	10/20/30	3,5-5



Model	Nominel luftstrøm (m ³ /h)	Elektrisk varme	
		Elektrisk opvarmingskapacitet 400Vx3 (kW)	Anbefalet installationshøjde (m)
ISB 2500 E	7140	12/22/34	3,5-5
ISB 3000 E	8160	16/26/42	3,5-5

Model	Nominel luftstrøm (m ³ /h)	Anbefalet installationshøjde (m)	Vandvarme		
			Opvarmingskapacitet 80 / 60°C (kW)	Opvarmingskapacitet 60 / 40°C (kW)	Opvarmingskapacitet 50 / 40°C (kW)
IBB 1000 P86	3750	5-7	18.21	-	-
IBB 1500 P86	5000	5-7	23.52	-	-
IBB 2000 P86	7500	5-7	36.57	-	-
IBB 2500 P86	8750	5-7	45.78	-	-
IBB 3000 P86	10000	5-7	55.04	-	-
ISB 1000 P86	2910	3,5-5	15.58	-	-
ISB 1500 P86	3880	3,5-5	19.71	-	-
ISB 2000 P86	5820	3,5-5	31	-	-
ISB 2500 P86	6790	3,5-5	38.97	-	-
ISB 3000 P86	7760	3,5-5	46.96	-	-
IBB 1000 P64	3750	5-7	-	15.16	-
IBB 1500 P64	5000	5-7	-	21.87	-
IBB 2000 P64	7500	5-7	-	31.13	-
IBB 2500 P64	8750	5-7	-	38.96	-
IBB 3000 P64	10000	5-7	-	45.49	-
ISB 1000 P64	2910	3,5-5	-	12.44	-
ISB 1500 P64	3880	3,5-5	-	18.55	-
ISB 2000 P64	5820	3,5-5	-	22.84	-
ISB 2500 P64	6790	3,5-5	-	31.79	-
ISB 3000 P64	7760	3,5-5	-	38.31	-
IBB 1000 P54	3750	5-7	-	-	16.48
IBB 1500 P54	5000	5-7	-	-	24.15
IBB 2000 P54	7500	5-7	-	-	35.04
IBB 2500 P54	8750	5-7	-	-	42.12
IBB 3000 P54	10000	5-7	-	-	49.27
ISB 1000 P54	2910	3,5-5	-	-	14.47
ISB 1500 P54	3880	3,5-5	-	-	21.19
ISB 2000 P54	5820	3,5-5	-	-	30.77
ISB 2500 P54	6790	3,5-5	-	-	36.94
ISB 3000 P54	7760	3,5-5	-	-	42.6

60Hz

Model	Uopvarmet	
	Nominel luftstrøm (m ³ /h)	Anbefalet installationshøjde (m)
IBB 1000 A	4020	5-7
IBB 1500 A	5360	5-7
IBB 2000 A	8040	5-7
IBB 2500 A	9380	5-7
IBB 3000 A	10720	5-7
ISB 1000 A	3060	3,5-5
ISB 1500 A	4080	3,5-5



Uopvarmet		
Model	Nominel luftstrøm (m ³ /h)	Anbefalet installationshøjde (m)
ISB 2000 A	6120	3,5-5
ISB 2500 A	7140	3,5-5
ISB 3000 A	8160	3,5-5

Elektrisk varme			
Model	Nominel luftstrøm (m ³ /h)	Elektrisk opvarmingskapacitet 400Vx3 (kW)	Anbefalet installationshøjde (m)
IBB 1000 E	4020	6/15/21	5-7
IBB 1500 E	5360	8/19/27	5-7
IBB 2000 E	8040	12/30/42	5-7
IBB 2500 E	9380	16/30/46	5-7
IBB 3000 E	10720	20/30/50	5-7
ISB 1000 E	3060	5/10/15	3,5-5
ISB 1500 E	4080	7,5/15/22,5	3,5-5
ISB 2000 E	6120	10/20/30	3,5-5
ISB 2500 E	7140	12/22/34	3,5-5
ISB 3000 E	8160	16/26/42	3,5-5

Vandvarme					
Model	Nominel luftstrøm (m ³ /h)	Anbefalet installationshøjde (m)	Opvarmingskapacitet 80 / 60°C (kW)	Opvarmingskapacitet 60 / 40°C (kW)	Opvarmingskapacitet 50 / 40°C (kW)
IBB 1000 P86	3750	5-7	18.21	-	-
IBB 1500 P86	5000	5-7	23.52	-	-
IBB 2000 P86	7500	5-7	36.57	-	-
IBB 2500 P86	8750	5-7	45.78	-	-
IBB 3000 P86	10000	5-7	55.04	-	-
ISB 1000 P86	2910	3,5-5	15.58	-	-
ISB 1500 P86	3880	3,5-5	19.71	-	-
ISB 2000 P86	5820	3,5-5	31	-	-
ISB 2500 P86	6790	3,5-5	38.97	-	-
ISB 3000 P86	7760	3,5-5	46.96	-	-
IBB 1000 P64	3750	5-7	-	15.16	-
IBB 1500 P64	5000	5-7	-	21.87	-
IBB 2000 P64	7500	5-7	-	31.13	-
IBB 2500 P64	8750	5-7	-	38.96	-
IBB 3000 P64	10000	5-7	-	45.49	-
ISB 1000 P64	2910	3,5-5	-	12.44	-
ISB 1500 P64	3880	3,5-5	-	18.55	-
ISB 2000 P64	5820	3,5-5	-	22.84	-
ISB 2500 P64	6790	3,5-5	-	31.79	-
ISB 3000 P64	7760	3,5-5	-	38.31	-
IBB 1000 P54	3750	5-7	-	-	16.48
IBB 1500 P54	5000	5-7	-	-	24.15
IBB 2000 P54	7500	5-7	-	-	35.04
IBB 2500 P54	8750	5-7	-	-	42.12
IBB 3000 P54	10000	5-7	-	-	49.27
ISB 1000 P54	2910	3,5-5	-	-	14.47
ISB 1500 P54	3880	3,5-5	-	-	21.19

