## Karakteristika



- Stilet, diskret og moderne design adaptive til vilkårlig interiørarkitektur.
- Glat front panel kan blive tilpasset med logotyper, lys, bogstaver eller sikkerheds- og informationsignal, alt efter kundekrav.
- Selvbærende stål afrundet beklædning med hjørneløse plastik sidebetræk., afsluttet i strukturel hvid epoxy-polyester maling RAL9016 som standard.Andre farver er tilgængelige ved anmodning.
- Skjult top luftindgang, undgå indersidesyn af enheden og indtaglamellerne.
- Anodiseret aluminium udtagslameller, airfoil formet.
- Lav støjniveau snoet kryds-strøm blæsere drevet af en 2-hastigheds ekstern rotor motor.
- "P" type with water heated coil and integrated regulation for ON/OFF or three stages 0-10V proportional valve. "E" type med elektrisk skjold elementer, tre faser med integreret regulering."A" type uden varme, kun luft.
- Advanced Plug&Play control. Includes: Advanced PRO control with LCD display and integrated thermostat, door contact, 7m RJ11 cable and remote control. Optional: intelligent Clever Pro Control (automatic, programmable, ModBus for PKC, timer, etc.)

## Specifikationer

50Hz

| | Uopvarmet | |
|---|---|---|
| **Model** | (m³/h) | (m) |
| ARIS 1000 A | 2,5-3,5 | |
| ARIS 1500 A | 2,5-3,5 | |
| ARIS 2000 A | 2,5-3,5 | |

| | Elektrisk varme | | |
|---|---|---|---|
| **Model** | (m³/h) | (kW) | (m) |
| ARIS 1000 E | 2,5-3,5 | | |
| ARIS 1500 E | 2,5-3,5 | | |
| ARIS 2000 E | 2,5-3,5 | | |

| | Vandvarme | | | |
|---|---|---|---|---|
| **Model** | (m³/h) | (kW) | (kW) | (m) |
| ARIS 1000 P86 | 2,5-3,5 | | | |
| ARIS 1500 P86 | 2,5-3,5 | | | |
| ARIS 2000 P86 | 2,5-3,5 | | | |
| ARIS 1000 P64 | 2,5-3,5 | | | |
| ARIS 1500 P64 | 2,5-3,5 | | | |
| ARIS 2000 P64 | 2,5-3,5 | | | |

60Hz

| | Uopvarmet | |
|---|---|---|
| **Model** | (m³/h) | (m) |
| ARIS 1000 A 60Hz | 2,2-2,8 | |
| ARIS 1500 A 60Hz | 2,2-2,8 | |
| ARIS 2000 A 60Hz | 2,2-2,8 | |

## Dimensioner



| | L | A | B |
|---|---|---|---|
| Aris 1000 | 1034 | 940 | - |
| Aris 1500 | 1534 | 1440 | - |
| Aris 2000 | 2034 | 1940 | 970 |




