



Karakteristika

Image not found or type unknown

TOP lufttæppe

- Innovative concept of decorative air curtain based on a recessed model to be installed free-hanging.
- Glat front panel kan blive tilpasset med logotyper, lys, bogstaver eller sikkerheds- og informationsignal, alt efter kundekrav.
- Self-supporting casing construction made of galvanized steel plate painted in grey RAL9006. Andre farver er tilgængelige ved anmodning.
- Inlet and Outlet inbuilt in the same grid painted in white RAL9016. Andre farver er tilgængelige ved anmodning.
- Anodiseret aluminium udtagslameller, airfoil formet.
- Lav støjniveau snoet kryds-strøm blæsere drevet af en 2-hastigheds ekstern rotor motor.
- "P" type with water heated coil and integrated regulation for ON/OFF or three stages 0-10V proportional valve. "E" type med elektrisk skjold elementer, tre faser med integreret regulering."A" type uden varme, kun luft.
- Advanced Plug&Play control. Includes: Advanced PRO control with LCD display and integrated thermostat, door contact, 7m and remote control. With integrated functions: door delay (configurable); interface mode; operation, alarm and maintenance warning signals; and multiple digital inputs that modify the air curtain's operation.
- Includes protective varnish for the electronic board and control.
- Optional:
 - Auxiliary temperature sensors that improve air curtain control and increase energy savings.
 - Clever PRO intelligent control (automatic, programmable, ModBus via PLC, timer, etc.) with an additional temperature sensor.

Specifikationer

50Hz

Uopvarmet			
Model	(m³/h)		(m)
TOP 1000 A	3.5		
TOP 1500 A	3.5		
TOP 2000 A	3.5		

Elektrisk varme			
Model	(m³/h)	(kW)	(m)
TOP 1000 E	3.5		
TOP 1500 E	3.5		
TOP 2000 E	3.5		

Vandvarme			
Model	(m³/h)	(kW)	(m)
TOP 1000 P86	3.5		
TOP 1500 P86	3.5		
TOP 2000 P86	3.5		
TOP 1000 P64	3.5		
TOP 1500 P64	3.5		
TOP 2000 P64	3.5		

Dimensioner

Image not found or type unknown

TOP lufttæppe Dimensioner